

SAFETY DATA SHEET

HI Document No 2.4.125, Revision 4



1. Identification

Product identifier	HyVolt II
Other means of identification	Not available.
Recommended use	Transformer Oil
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer:	Ergon Refining
Address:	2611 Haining Rd Vicksburg, Mississippi 39183
Contact Name:	Will Poe
Telephone:	1.601.630.8319
E-mail:	will.poe@ergon.com
Emergency Contacts	
Ergon Refining:	1.601.638.4960 Normal Business Hours
Chemtrec:	1.800.424.9300 After Business Hours (North America Only) 1.703.527.3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	May be fatal if swallowed and enters airways.
Prevention	Do not breathe gas/mist/vapors/spray.
Response	IF exposed or concerned: Get medical advice/attention.
Storage	Store in accordance with local/regional/national/international regulation.
Disposal	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. See section 13 of this SDS for disposal instructions.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC		64742-53-6	59.7 - 99.9
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC		64742-55-8	0 - 40
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC		64742-56-9	0 - 20

Chemical name	Common name and synonyms	CAS number	%
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)]		128-37-0	< 0.3

4. First-aid measures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.
Skin contact	Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact	Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Contact physician if discomfort continues.

5. Fire-fighting measures

Suitable extinguishing media	Halon. Dry chemicals. Foam. Carbon dioxide (CO ₂). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire-fighting equipment/instructions	Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurized air mask if product is involved in a fire.
General fire hazards	No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.
Methods and materials for containment and cleaning up	Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling	DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value	Form
HyVolt II (CAS Mixture)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Adequate ventilation should be provided whenever the material is heated or mists are generated. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Goggles/face shield are recommended.
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.
Respiratory protection	Under normal conditions, respirator is not normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Not available.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Color	Water White to Pale
Odor	Mild Petroleum Odor
Odor threshold	Not available.
pH	Not applicable
Melting point/freezing point	< -40 °F (< -40 °C) ASTM D 5949
Initial boiling point and boiling range	> 460 °F (> 237.78 °C) ASTM D 2887/ ISO 3294
Flash point	>= 293.0 °F (>= 145.0 °C) Cleveland Open Cup ASTM D 92/ ISO 2592
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.89 (59 °F (15 °C) ASTM D 4052/ ISO 12185)
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	> 599 °F (> 315 °C) ASTM E 659
Decomposition temperature	Not available.
Viscosity	9.3 cSt (104 °F (40 °C) ASTM D 445)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.

Hazardous decomposition products Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration. May be fatal if swallowed and enters airways.

Inhalation May be fatal if swallowed and enters airways.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

Symptoms related to the physical, chemical and toxicological characteristics Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.

Information on toxicological effects

Acute toxicity Not applicable.

Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)		
Acute		
<i>Oral</i>		
LD50	Guinea pig	10700 mg/kg
	Mouse	1040 mg/kg
	Rat	890 mg/kg

Not available. * Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye irritation Not classified. May cause minor irritation on eye contact.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Nota L - Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346. Not classified.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further information Risk of chemical pneumonia after aspiration.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
HyVolt II (CAS Mixture)		
Crustacea	EC50 Daphnia	863.8272 mg/l, 48 hours estimated

Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex)
		1.44 mg/l, 48 hours

Not available. * Estimates for product may be based on additional component data not shown.

Persistence and degradability	Not inherently biodegradable.
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
Mobility in soil	Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Hazardous waste code	Not applicable.
Waste from residues / unused products	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List. CERCLA/SARA Hazardous Substances - Not applicable.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
SARA 302 Extremely hazardous substance	Not listed.
SARA 311/312 Hazardous chemical	No
SARA 313 (TRI reporting)	Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-13-2014

Revision date 05-06-2014

Version # 02

References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Chemical Abstracts Service Registry Handbook
CRC: Handbook of Chemistry and Physics
ILO Safety Cards
International Labour Organization
International Maritime Organization Marine Pollutants List
NFPA Hazardous Chemical Data Sheets
NIOSH Pocket Guide
Registry of Toxic Effects of Chemical Substances (RTECS)
US DOT Hazardous Materials Regulations

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Physical & Chemical Properties: Multiple Properties
Physical and chemical properties: Appearance
Toxicological Information: Toxicological Data
Toxicological information: Skin contact
Toxicological information: Corrosivity
Regulatory Information: Risk Phrases - Labeling
GHS: Classification

SAFETY DATA SHEETNAME OF PRODUCT *HYTRANS 61***SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: HYTRANS 61
SYNONYMS: DISTILLATE, PETROLEUM
PRODUCT CODE: 2791
MANUFACTURER: SAN JOAQUIN REFINING CO., INC
DIVISION: BAKERSFIELD
ADDRESS: P.O. BOX 5576, BAKERSFIELD, CA., 93388
EMERGENCY PHONE: (661) 327-4257
RECOMMENDED USE: TRANSFORMER OIL
RESTRICTIONS ON USE: NOT INTENDED TO BE USED AS A FUEL
PREPARED BY: SAN JOAQUIN REFINING CO., INC. HEALTH, SAFETY AND ENVIRONMENTAL DEPARTMENTS

SECTION 2: HAZARDS IDENTIFICATION

ROUTES OF ENTRY:	EYES: Yes	SKIN: Yes	INGESTION: Yes	INHALATION: Yes
-------------------------	------------------	------------------	-----------------------	------------------------

OSHA Hazard: irritant



Signal word: Warning
 GHS Classification: 2

Skin & eye irritant reversible adverse effects = GHS Cat. 2

POTENTIAL HEALTH EFFECTS:

- EYES:** Eye contact may result in irritation and redness. Exposure to high concentrations of vapors may be irritating to the eyes.
SKIN: Prolonged and repeated contact can defat the skin, which may result in dryness, dermatitis and cracking of the skin.
INGESTION: Do not ingest. Ingestion may result in nausea or stomach discomfort. If swallowed do not induce vomiting, call a physician.
INHALATION: Fumes may be unpleasant and may produce nausea. Remove the person to fresh air if respiratory discomfort occurs.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Persons with preexisting skin or respiratory disorders may have their conditions aggravated by overexposure to this material.

SECTION 3: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION**CHEMICAL FAMILY:** DISTILLATE (PETROLEUM) HYDROTREATED LIGHT NAPHTHENIC

HAZARDOUS COMPONENT(S)	CAL-OSHA PEL- TWA (8 HOUR)	ACGIH TLV-TWA (8 HOUR)	OTHER LIMITS RECOMMENDED	% BY WEIGHT
Distillates, Petroleum, Hydrotreated Light Naphthenic CAS No. 64742-53-6	5 mg/m ³ (As oil mist)	5 mg/m ³ (As oil mist)	None	>99
2, 6-Di-t-butyl-p-cresol (BHT) CAS No. 128-37-0	5 mg/m ³ (Nuisance Particulates)	2 mg/m ³ (Inhalable aerosol and/or vapor)	10 mg/m ³	<1

SECTION 4: FIRST AID MEASURES

EYES:	Avoid contact with eyes. If contact occurs, immediately flush eyes with water for a minimum of 15 minutes. Seek medical attention immediately.
SKIN:	Avoid contact with skin. If contact occurs, wash contact areas with soap and water. Remove and clean oil soaked clothing daily and wash affected area.
INGESTION:	Do not induce vomiting. If ingested, seek medical attention.
INHALATION:	Not expected to be a problem. However, if respiratory irritation, dizziness, nausea or unconsciousness occurs due to excessive vapor or mist exposure, seek medical attention. If operating conditions create airborne concentrations that exceed the exposure standard, the use of an approved NIOSH/OSHA respirator for organic vapors or air-supplied breathing equipment is recommended.

SECTION 5: FIREFIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, (% BY VOLUME)	UPPER: No data available LOWER: No data available
FLASH POINT: COC °F:	293° Minimum
EXTINGUISHING MEDIA:	Foam, water fog, dry chemical, CO ²
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire space without proper protective equipment including self-contained breathing apparatus. See Hazardous Decomposition Products.
HAZARDOUS DECOMPOSITION PRODUCTS:	Normal combustion forms carbon dioxide and water vapor, and may produce oxides of sulfur and nitrogen. Incomplete combustion can produce carbon monoxide.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION:	Wear safety glasses, rubber gloves, Tyvek type coveralls and rubber boots.
ACCIDENTAL RELEASE MEASURES:	In case of spill, clean up using absorbent material such as earth or sand.
RCRA HAZARD CLASS:	This product is not a characteristic hazardous waste under RCRA. No EPA waste numbers are applicable for this product's components.

SECTION 7: HANDLING AND STORAGE

PERSONAL PROTECTION:	Wear safety glasses, rubber gloves, Tyvek type coveralls and rubber boots.
HANDLING AND STORAGE:	Avoid fire, sparks or open flame. Wear appropriate personal protective equipment to ensure that this product does not contact the eyes or skin.
VENTILATION:	Use adequate ventilation to keep the airborne concentrations of this material below the established exposure standard.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:	If operating conditions create airborne concentrations that exceed the exposure standard for this product, the use of an approved NIOSH/OSHA respirator for organic vapors or air supplied breathing equipment is recommended.
EYE PROTECTION:	Wear appropriate safety glasses, goggles or full-face shield.
SKIN PROTECTION:	Long sleeve cotton shirt and cotton pants are recommended. Wear appropriate gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Straw colored liquid	UPPER/LOWER FLAM/EXP LMT:	NDA
ODOR:	Petroleum odor	VAPOR PRESSURE (mmHg):	@ 100° F < 0.1
ODOR THRESHHOLD:	NDA	VAPOR DENSITY (AIR = 1):	4
pH:	NDA	RELATIVE DENSITY:	NDA
MELTING/FREEZING PT:	-40°F Max	SOLUBILITY IN WATER:	NIL
INITIAL BOILING POINT: @760° mmHg:	560° F	PART. COEF. N-OCT/H2O	≥5.7
FLASH POINT: COC °F:	293° Minimum	AUTOIGNITION TEMP:	NDA
EVAPORATION RATE (ETHYL ETHER = 1):	<1	DECOMPOSITION TEMP:	NDA
FLAMMABILITY (solid, gas):	NA	SPECIFIC GRAVITY (H2O = 1):	0.88
PERCENT VOLATILE (% BY VOL.):	0		

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable
CONDITIONS CONTRIBUTING TO INSTABILITY:	None
INCOMPATIBILITY (MATERIAL TO AVOID):	May react with strong oxidizers.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	Normal combustion forms carbon dioxide and water vapor, and may produce oxides of sulfur and nitrogen. Incomplete combustion can produce carbon monoxide.
HAZARDOUS POLYMERIZATION:	Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE STUDIES:	Low order of acute oral or dermal toxicity
HEALTH EFFECTS:	Mild eye and skin irritant
CARCINOGENICITY:	ACGIH, NTP, OSHA and IARC carcinogen lists were checked for those components with CAS Registry Numbers (64742-53-6) & (128-37-0).
ACGIH:	This product is not listed as carcinogenic.
IARC:	The International Agency for research on cancer has concluded that highly or severely refined light and middle distillates are Group 3 substances, "not classifiable as to their carcinogenicity to humans," based on inadequate human or animal evidence.
NTP:	This product is not listed as carcinogenic.
OSHA:	This product is not listed as carcinogenic.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY:	No mortality or other adverse reactions to the exposures during or after 96 h.
PERSISTENCE & DEGRADABILITY:	Direct photolysis will not contribute to a measurable degradative removal of chemical components in this category from the environment.
BIOACCUMULATIVE POTENTIAL:	Inherently biodegradable
MOBILITY IN SOIL:	NDA
OTHER ADVERSE EFFECTS:	NDA
AQUATIC RELEASE:	Advise authorities if product has entered or may enter watercourses or sewer drains.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE RESIDUES DESCRIPTION:	This product is not a characteristic hazardous waste under RCRA. No EPA waste numbers are applicable for this product's components.
SAFE HANDLING INFORMATION:	See Section 7 (Handling and Storage)
WASTE DISPOSAL METHOD:	Observe Federal, State and Local regulations covering chemical waste spills.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION:

PROPER SHIPPING NAME:	Not regulated as a hazardous material for transportation by USA DOT.
------------------------------	--

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA (TOXIC SUBSTANCE CONTROL ACT) REGISTRY: Listed

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT):
This product is not a hazardous substance under CERCLA.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

302/304 This product is not listed as an extremely hazardous substance in 40 CFR Part 355, and is not known to contain an extremely hazardous substance in a concentration greater than one percent by weight.

311/312 HAZARD CATEGORIES:

Acute Health Hazard:	No
Chronic Health Hazard:	No
Fire Hazard:	No
Pressure Release Hazard:	No
Reactivity Hazard:	No

313 This product is not known to contain any components in concentrations above OSHA *de minimus* levels that are listed as toxic in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA.

WHMIS: Listed

OSHA: 29 CFR 1910.1200 (Hazard Communication) required.

STATE REGULATIONS:

Distillate, Petroleum, Hydrotreated Light Naphthenic appears on the following state hazardous substances list.

MA

SECTION 16: OTHER INFORMATION

DATE REVISED: 7/1/14

SUPERCEDES: 1/11/13

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HMIS® HAZARD RATING	
4 - SEVERE	HEALTH 1
3 - SERIOUS	FLAMMABILITY 1
2 - MODERATE	REACTIVITY 0
1 - SLIGHT	
0 - MINIMAL	

The information provided in this Material Safety Data Sheet is believed to be accurate and reliable on and as of the date on page one. **However, this Material Safety Data Sheet is not a guarantee or warranty of any kind, express or implied. Any and all warranties of merchantability and/or fitness for a particular purpose are specifically disclaimed.** It is the user's responsibility to determine the conditions under which the product is used, including the selection of engineering controls, work practices and Personal Protective Equipment to minimize hazards.