



Micro-Power

0.5 through 3KVA

Oil-Filled Pole-Mounted Distribution Transformers

Howard Industries Micro-Power is a compact and light-weight, oil-filled pole-mounted distribution transformer designed to serve small, isolated loads. Typical applications include capacitor banks, reclosers, station control power, billboards, microwave and cellular tower sites, water pumps, security lights, street lights, traffic signals, and railroad signals. Micro-Power transformers provide an economical alternative to larger standard size transformers in a lightweight package starting at under 100 pounds.

Ratings

- 0.5, 1, 1.5, or 3 kVA (65° C rise)
- High-voltage: 2400/4160Y through 19920/34500GrdY (2 HV bushings) or 4160GrdY/2400 through 34500GrdY/19920 (1 HV bushing)
- Low-voltage: 120 (1 or 2 LV bushings), 120/240 (3 LV bushings), 240 (1 or 2 LV bushings), 240/480 (3 LV bushings), or 277 (1 or 2 LV bushings)

Standard Features

- Mild steel tank, cover, and clamp ring
- Tough powder paint finish that resists abrasion and corrosion
- 10 kV minimum insulation on cover and clamp ring
- Continuously welded hanger brackets and lifting lugs for safety and corrosion resistance



- Corrosion resistant hardware on clamp ring
- Recessed tank bottom for scuff protection
- Shell-type core/coil construction
- Wound core construction with step-lap joints for high efficiency
- Porcelain high-voltage bushing(s) with tin plated bronze eyebolt terminal(s)
- Molded polymer or porcelain low-voltage bushing(s) with tin plated bronze terminal(s)
- Low-voltage neutral ground strap (on transformers with one HV bushing)
- Visible cover ground with disconnect
- Tank ground provision
- Tank ground connector (on transformers with one HV bushing)
- Automatic pressure relief device
- Mineral oil dielectric coolant with oxidation inhibitor
- KVA decal on tank
- Internal oil level mark
- Laser engraved anodized aluminum name plate

Optional Features


- Five-pin low-voltage receptacle
- External MOV lightning arrester or mounting provisions only
- Wildlife protection
- Tank ground connector
- Low-voltage neutral ground strap




1. HV bushing (1 or 2 bushings)
2. LV bushing (1,2 or 3 bushings; or 5-pin connector)
3. Mounting bracket, ANSI Type A (1, 2, or 4 brackets)
4. Lifting hook (2)
5. Tank ground nut
6. Nameplate
7. Cover clamping ring
8. LV neutral ground nut
9. Cover ground strap
10. Automatic pressure relief device




120
240
277
Note (1)




120
240
277



Optional mounting bracket



120/240 or 240/480



Optional mounting brackets

BIL	Dimensions				
	A	B	C	D Note (4)	E Note (6)
60-95	26"	14"	17"	8"	17/19"
125	26"	14"	17"	12"	17/19"
150	31"	16"	19"	12"	22"

KVA	Approx. Weight (Lbs.)		
	60-95 KV BIL	125 KV BIL	150 KV BIL
0.5	95	100	130
1.0	95	110	140
1.5	100	115	140
3.0	125	125	160

NOTES:

- 1) Five-pin low-voltage receptacle also available
- 2) External surge arrester and internal expulsion fuse available as options
- 3) Low-voltage circuit breaker not available
- 4) Dimension "D" may be less than indicated if lower mounting bracket(s) requested
- 5) Spacing may be less than 11.25" if tank height (Dimension E) is less than 19"



Howard Industries, Inc.
Certified to ISO 9001:2015
10002179